



Low VF Bridge Rectifiers



Features

- Glass Passivated Chip Junction
- Low IRRM
- Low VF
- High VRRM

Benefits

- Case: GBU
- Terminals: Solderable Per MIL-STD-750
- Reduced power loss and switching transistor
- Reduced snubbing


Maximum Ratings and Electrical characteristics

Ratings at 25 °C ambient temperature unless otherwise specified.


Single phase half-wave 60 Hz, resistive or inductive load, for capacitive load current derate by 20 %.

Parameter	Symbols	GBU15L06	Units
Maximum Repetitive Peak Reverse Voltage	VRRM	600	V
Maximum RMS voltage	VRMS	420	V
Maximum DC Blocking Voltage	VDC	600	V
Average Rectified Output Current	Io	15.0	A
Peak Forward Surge Current 8.3 ms Single Half Sine Wave Superimposed on Rated Load (JEDEC Method)	IFSM	250	A
Maximum Forward Voltage at 7.5 A	VF	0.93	V
Maximum DC Reverse Current @TA=25 °C at Rated DC Blocking Voltage @TA=125 °C	IR	10 500	μA
Typical Junction Capacitance (Note1)	Cj	25	pF
Operating and Storage Temperature Range	Tj, Tstg	-55 ~ +150	°C
Note: 1. Measured at 1MHz and applied reverse voltage of 4 VDC. 2. Mounted on glass epoxy PC board with 4 × 1.5 ± 1.5 (3.81 × 3.81 cm) copper pad			


RATINGS AND CHARACTERISTICS CURVES (TA = 25 °C unless otherwise noted)




Current Derating, Case



Typical Junction Capacitance




Typical Forward Voltage




Typical Reverse Current


PACKAGE OUTLINE DIMENSIONS



GBU		
Dim	Min	Max
A	21.70	22.50
B	3.40	4.10
C	7.40	8.00
D	1.65	2.26
E	2.25	2.85
F	2.05	2.4
G	1.02	1.37
H	4.83	5.43
J	17.0	18.6
L	18.3	18.9
M	3.30	3.66
N	0.46	0.66



Marking Information



①W : Company's trademark


②Product model : GBU15L06

③PDC information:


Y X WW H
 Y:Year code(ex:0=2020)
 X:Internal identification code
 WW:Week code(01 to 53)
 H:Halogen-free

Packaging Information

1.Inside Box



2.Outside Box



Packaging Information

NO	UNIT	Inside Box			Outside Box		
		L1	W1	H1	L2	W2	H2
Size	mm	228	110	43	460	240	235
QTY	PCS	250PCS/carton			5,000PCS/carton,20boxes in total		
Note	Tolerance	≤20mm,±3mm; 21-100mm,±5mm; 101-500mm,±10mm					