



Ultra Low VF Bridge Rectifiers

VF:0.71V@1A/125℃



Features

- Glass Passivated Chip Junction
- Low IRRM
- Ultra Low VF
- High VRRM

Benefits

- Case: GBU
- Terminals: Solderable Per MIL-STD-750
- Reduced power loss and switching transistor
- Reduced snubbing

Maximum Ratings and Electrical characteristics

Ratings at 25 °C ambient temperature unless otherwise specified.

Single phase half-wave 60 Hz, resistive or inductive load, for capacitive load current derate by 20 %.

Parameter		Symbols	GBU8V06		Units
Maximum Repetitive Peak Reverse Voltage		VRRM	600		V
Maximum RMS voltage		VRMS	420		V
Maximum DC Blocking Voltage		VDC	600		V
Average Rectified Output Current		Io	8.0		A
Peak Forward Surge Current 8.3 ms Single Half Sine Wave Superimposed on Rated Load (JEDEC Method)		IFSM	200		A
Instantaneous forward voltage per diode	IF=1A	Tj=25℃	TYP.	MAX.	V
	IF=1A	Tj=125℃	0.80	0.82	
	IF=4A	Tj=25℃	0.71	--	
	IF=4A	Tj=25℃	0.86	0.88	
	IF=4A	Tj=125℃	0.78	--	
Maximum DC Reverse Current @TA=25℃ at Rated DC Blocking Voltage @TA=125℃		IR	5 100		μA
Typical Junction Capacitance (Note1)		Cj	25		pF
Operating and Storage Temperature Range		Tj, Tstg	-55 ~ +150		℃

Note: 1. Measured at 1MHz and applied reverse voltage of 4 VDC.

RATINGS AND CHARACTERISTICS CURVES (TA = 25 °C unless otherwise noted)

Fig.1 Current Derating, Case




Fig.2 Maximum Non-Repetitive Peak Forward Surge Current




Fig.3 Typical Forward Voltage






Fig.4 Typical Reverse Characteristics




PACKAGE OUTLINE DIMENSIONS




GBU		
Dim	Min	Max
A	21.70	22.50
B	3.40	4.10
C	7.40	8.00
D	1.65	2.26
E	2.25	2.85
F	2.05	2.4
G	1.02	1.37
H	4.83	5.43
J	17.0	18.6
L	18.3	18.9
M	3.30	3.66
N	0.46	0.66

Marking Information




Packaging Information

1. Inside Box



2. Outside Box



Packaging Information

NO	UNIT	Inside Box			Outside Box		
Size	mm	L1	W1	H1	L2	W2	H2
		228	110	43	460	240	235
QTY	PCS	250PCS/carton			5,000PCS/carton,20boxes in total		
Note	Tolerance ≤20mm,±3mm; 21-100mm,±5mm; 101-500mm,±10mm						