


Ultra Low Leakage Current Rectifier Schottky

Ultra Low IR:5uA@125°C

SS2P60AF

SMAF



Features

- Low forward voltage drop
- Ultra Low Leakage Current 5uA@125°C
- High efficiency operation
- Lead Free Finish, RoHS Compliant


Applications

- DC/DC Converters
- AC/DC Adaptors
- Switching Power Supplies
- Freewheeling Diodes


Maximum ratings and electrical characteristics (TJ = 25°C unless otherwise noted)

Parameter			Symbol	Limit		Unit
Maximum repetitive peak reverse voltage			VRRM	60		V
Maximum average forward rectified current			IF(AV)	2		A
Peak forward surge current 8.3 ms single half sine- wave superimposed on rated load per diode			IFSM	50		A
Operating junction and storage temperature range			TJ, TSTG	-50 to +150		°C
Typical thermal resistance per diode(Mounted on FR-4 PCB)			RθJC	20		°C/W
Instantaneous forward voltage per diode			VF	TYP.	MAX.	V
	IF=2A	TJ=25°C		0.90	0.95	
	IF=2A	TJ=125°C		0.86	-	
Instantaneous reverse current per diode at rated reverse voltage		TJ=25°C	IR	-	1	uA
		TJ=125°C		5	-	uA


RATINGS AND CHARACTERISTICS CURVES (TA = 25 °C unless otherwise noted)




Current Derating, Case



Maximum Repetitive Surge Current




Typical Forward Voltage



Typical Reverse Current

PACKAGE OUTLINE DIMENSIONS


SMAF



SMAF mechanical data


UNIT		A	B	C	D	E	F	G
mm	max	1.10	0.95	0.25	2.8	3.9	4.9	1.65
	min	0.85	0.50	0.11	2.2	3.2	4.2	1.20
mil	max	43.30	37.40	9.84	110.24	153.54	192.91	64.96
	min	33.46	19.68	4.33	86.61	125.98	165.35	47.24

SMAF Suggested Pad Layout




UNIT		P1	P2	Q1	Q2
mm	min	5.10	1.50	1.7	1.8
mil	min	200.8	59.05	67.0	70.87

Marking Information




①Product model : SS2P60AF is abbreviated to SS2P60

②PDC information:





Packaging Information


1.Reel Dimensions



2. Inside Box



3. Outside Box



Packaging Information

NO	UNIT	Reel Dimensions			Inside Box			Outside Box		
Size	mm	φ	A	B	L1	W1	H1	L2	W2	H2
		178	55	11	180	183	120	270	375	235
QTY	PCS	Smallest package,3000PCS/reel			30,000PCS,10reel in total			120,000PCS/carton,4boxes in total		
Note	Tolerance ≤20mm,±3mm; 21-100mm,±5mm; 101-500mm,±10mm									