




SCHOTTKY BARRIER RECTIFIER

TO-220AB
MBR60100CT



ITO-220AB
MBR60100CTF



Features

- Low forward voltage drop
- Low power losses
- High efficiency operation
- Lead Free Finish, RoHS Compliant

Applications

- DC/DC Converters
- AC/DC Adaptors
- Switching Power Supplies
- Freewheeling Diodes

Maximum ratings and electrical characteristics (T_J = 25°C unless otherwise noted)

Parameter			Symbol	Limit		Unit
Maximum repetitive peak reverse voltage			VRRM	100		V
Maximum average forward rectified current	per device	IF(AV)	30		A	
	per diode		60			
Peak forward surge current 8.3 ms single half sine- wave superimposed on rated load per diode			IFSM	350		A
Operating junction and storage temperature range			TJ, TSTG	-55 to +150		°C
Typical thermal resistance per leg	TO-220AB		RθJC	2		°C/W
	ITO-220AB			4		°C/W
Instantaneous forward voltage per diode			VF(1)	TYP.	MAX.	V
	IF=3A	TJ=25°C		0.60	0.65	
	IF=3A	TJ=125°C		0.50	-	
	IF=30A	TJ=25°C		0.85	0.90	
	IF=30A	TJ=125°C		0.76	-	
Instantaneous reverse current per diode at rated reverse voltage		TJ=25°C	IR(2)	1	20	uA
		TJ=125°C		1	-	mA

Notes:

(1) Pulse test: 300 μs pulse width, 1 % duty cycle

(2) Pulse test: Pulse width ≤ 40 ms

RATINGS AND CHARACTERISTICS CURVES (TA = 25 °C unless otherwise noted)




Fig. 1 - Forward Derating Curve




Fig. 2 - Maximum Non-Repetitive Peak Forward Surge Current Per Diode




Fig. 3 - Typical Instantaneous Forward Characteristics Per Diode




Fig. 4 - Typical Reverse Characteristics Per Diode





Fig. 5 - Typical Junction Capacitance Per Diode


PACKAGE OUTLINE DIMENSIONS

Note:unit In(mm)


TO-220AB



ITO-220AB




Marking Information



- ①W : Company's trademark
- ②Product model : MBR60100CT or MBR60100CTF
- ③PDC information :
 Y X WW
 WW:Week code(01 to 53)
 X:Internal identification code
 Y:Year code(ex:0=2020)
- ④  Double wafer



Packaging Information

1.Tube Dimensions



2. Inside Box

3. Outside Box



Packaging Information

NO	UNIT	Tube Dimensions			Inside Box			Outside Box		
Size	mm	A	B	C	L1	W1	H1	L2	W2	H2
		530	7	33	570	46	150	590	260	180
QTY	PCS	50PCS/Tube			Smallest package,1000PCS, 20 tube in total			5,000PCS/carton,5 boxes in total		
Note	Tolerance ≤20mm,±3mm; 21-100mm,±5mm; 101-500mm,±10mm									