


Ultra Low Leakage Current Rectifier Schottky

Ultra Low IR:5uA@125°C

SS5P100ASP

TO-277



Features

- Advanced trench technology
- Low forward voltage drop
- Ultra Low Leakage Current 1uA Max
- High efficiency operation
- Lead Free Finish, RoHS Compliant


Applications

- DC/DC Converters
- AC/DC Adaptors
- Switching Power Supplies
- Freewheeling Diodes


Maximum ratings and electrical characteristics (TJ = 25°C unless otherwise noted)

Parameter			Symbol	Limit		Unit
Maximum repetitive peak reverse voltage			VRRM	100		V
Maximum average forward rectified current			IF(AV)	5.0		A
Peak forward surge current 8.3 ms single half sine- wave superimposed on rated load per diode			IFSM	150		A
Operating junction and storage temperature range			TJ, TSTG	-50 to +150		°C
Typical thermal resistance per diode(Mounted on FR-4 PCB)			RθJC	72		°C/W
Instantaneous forward voltage per diode			VF	TYP.	MAX.	V
	IF=3A	TJ=25°C		0.85	0.88	
	IF=3A	TJ=125°C		0.80	-	
	IF=5A	TJ=25°C		0.93	0.95	
	IF=5A	TJ=125°C		0.86	-	
Instantaneous reverse current per diode at rated reverse voltage		TJ=25°C	IR	-	1	uA
		TJ=125°C		5	-	uA


RATINGS AND CHARACTERISTICS CURVES (TA = 25 °C unless otherwise noted)




Current Derating, Case



Maximum Repetitive Surge Current




Typical Forward Voltage



Typical Reverse Current

PACKAGE OUTLINE DIMENSIONS


TO-277



TO-277 mechanical data


UNIT		A	A2	b1	b2	D	D1	e	E	E1	E2	L	L1
mm	max	1.3	0.4	1.0	1.9	4.3	3.05	2.0	6.6	5.75	3.55	1.0	0.7
	min	1.1	0.2	0.8	1.7	3.9		1.8	6.4	5.3		0.8	0.5
mil	max	51.18	15.75	39.37	74.80	169.3	120.0	78.74	259.8	226.3	139.7	39.37	27.55
	min	43.30	7.87	31.49	66.93	153.5		70.86	252.0	208.6		31.49	19.69

TO-277 Suggested Pad Layout



UNIT		C	G	X	X1	Y	Y1
mm	min	1.80	0.90	3.4	1.4	4.9	1.4
mil	min	78.86	35.43	133.86	35.43	192.91	55.12

Marking Information



① Product model :SS5P100ASP Referred to as 5P100

② PDC information :

Y X WW



WW:Week code(01 to 53)

X:Internal identification code


Y:Year code(ex:0=2020)

Packaging Information


1.Reel Dimensions



2. Inside Box



3. Outside Box



Packaging Information

NO	UNIT	Reel Dimensions			Inside Box			Outside Box		
Size	mm	φ	A	B	L1	W1	H1	L2	W2	H2
		330	70	15	335	335	43	360	360	360
QTY	PCS	Smallest package,5000PCS/reel			10,000PCS,2 reel in total			80,000PCS/carton,8 boxes in total		
Note	Tolerance ≤20mm,±3mm; 21-100mm,±5mm; 101-500mm,±10mm									